

LORAMS: Sharing Learning Experiences with Social and Ubiquitous Media

Hiroaki Ogata, Toru Misumi, Bin Hou, Mengmeng Li, Moushir El-Bishouty and Yoneo Yano

Department of Information Science and Intelligent Systems

University of Tokushima

Tokushima, Japan

PRESTO, JST

Tokyo

ogata@is.tokushima-u.ac.jp

Abstract— This paper proposes a personal learning assistant called LORAMS (Link of RFID and Movies System), which supports learners with a system to share and reuse learning experiences by linking movies to environmental objects. We assume that every object has RFID tags and mobile devices have a RFID reader and can record a video at anytime and anyplace. By scanning RFID tags of real objects, LORAMS can provide only video segments that include the objects. Also LORAMS recommends the similar videos to be compared. In LORAMS, the video recording and RFID tagging are used purposely to support further teaching or learning rather than “just record it and use it in some day”. We think that LORAMS can be applied to various kinds of domains that employ several kinds of real objects and vary the results depending on the combination of the objects; for example, cooking, checking upon cars such as oils, battery, and tires, surgery operations and chemical bioreactor experimentations.

Index Terms— Ubiquitous Learning, Life log, mobile learning, RFID tags

I. INTRODUCTION

Ubiquitous computing [1] will help organize and mediate social interactions wherever and whenever these situations might occur [3]. Its evolution has recently been accelerated by improved wireless telecommunications capabilities, open networks, continued increases in computing power, improved battery technology, and the emergence of flexible software architectures [6]. With those technologies, CSUL (Computer Supported Ubiquitous Learning) is realized, where an individual and collaborative learning in our daily life can be seamlessly included [4,5].

One of the most important ubiquitous computing technologies is the RFID (radio frequency identification) tag, which is a rewritable IC memory with non-contact communication facility. This cheap, tiny RFID tag makes it possible to tag almost everything, replaces the barcode, helps computers to be aware of their surrounding objects by themselves, and thereby detects some aspects of the user’s [2].

We assume that almost all the products will be attached with RFID tags in the near future, where we will be able to learn at anytime at anyplace from every object by scanning its

RFID tag. Also we think that almost mobile devices will have a video camera and record a video.

The fundamental issues of CSUL are

- How to capture and share learning experiences that happen at anytime and anyplace.
- How to retrieve and reuse them for learning.

As for the first issue, video recording with handheld devices will allow us to capture learning experiences. Also social media services such as YouTube [<http://www.youtube.com/>] helps to share the user generated videos. The second issue will be solved, by identifying objects in a video with RFID so that the system can recommend the videos in similar situations to the situation where the learner has a problem.

This paper proposes LORAMS (Linking of RFID and Movie System) for CSUL. There are two kinds of users in this system. One is a provider who records his/her experience into videos. The other is a user who has some problems and retrieves the videos. In this system, a user uses his/her own PDA with RFID tag reader and digital camera, and links real objects and the corresponding objects in a movie and shares it among other learners. Scanning RFID tags around the learner enables us to bridge the real objects and their information into the virtual world. LORAMS detects the objects around the user using RFID tags, and provides the user with the right information in that context.

In the previous work, we developed LORAMS using RealPlayer and applied the systems for computer assembling (Ogata, Matsuka, El-Bishouty & Yano, 2007). From the evaluation, RFID is very useful for identifying objects precisely. However, we found that LORAMS system should support annotations for sharing knowledge and comparing videos. In this paper, LORAMS system has been improved in order to utilize the full advantage of RFID to share and compare personal experiences for ubiquitous learning.

II. LORAMS

A. Design

The characteristics of LORAMS are as follows:

- The learner’s experience is recorded into a video and linked to RFID tags of real objects. The video can be

shared with other learners. Therefore, it is not necessary to add keywords or annotations into a video and is easy to make an index of the video to be shared with other learners.

- Learners can find suitable videos by scanning RFID tags of real objects around them without entering any keyword.
- Based on ratings by learners and the system, the results are listed.

There are three phases for LORAMS as follows:

- Video recording phase
- Video search phase
- Video replay and compare phase

The video recording process requires a PDA, an RFID tag reader, a video camera, and wireless access to the Internet. First, a user has to start recording video at the beginning of the task. Before using objects, the user scans RFID tags and the system automatically sends the data and its time stamp to the server. After completing the task, the user uploads the video file to the server and the server automatically generates an SMIL (Synchronized Multimedia Integration Language) file to link the video and the RFID tags.

On the other hand, video search and reply processes need a PDA, an RFID tag reader, and a video player. The user scans RFID tags around him/her and/or enters keywords of the objects, and then the system sends them to the server and shows the list of the videos that match the objects and keywords. The system, moreover, extracts a part of the video that matches with these objects.

B. User Interface

In the recoding phase, the user uses PDA, in that RFID tag reader is attached. Before usage, the user sets up the information on the RFID reader such as port number and code type, and enters the user name. When the user uses an object, s/he scans the RFID of the object. Also, when the user finishes using the object, s/he scans the RFID of the object. The RFIDs and the time stamps of the scans are sent to the server from the PDA. When the recorded video is uploaded, the time stamp of scanning RFIDs are linked to the video by the absolute time and date.

By entering keywords and/or scanning RFID tags of physical objects in (A) in figure 1, video search starts. LORAMS starts to search videos and shows the video in order of a appropriateness. The list in (C) shows the videos that have been registered recently. By selecting a video from the list (B), the video playback window appears. The video title, the author's name, and the recorded date are shown in (D), and all the objects are listed in (E) in time order. By clicking an item in the list, the system jumps to the video segment that includes the selected item. Pictures of the

items are shown in (F). By clicking one of the pictures, the system shows to the video segments that include the selected item. Playback (such as fast-forward) is controlled by the tool bar in (G). Videos similar to the playing video are listed in (H).



Figure 1. Video search interface.

User can compare two different videos in the window as shown in figure 4. For example, the left is a video of an expert, and the right is a video of the user after the user watched the expert's video. The tile of the video is shown in (A) and the video is replayed in (B). The timeline of the left video is shown in (D) and that of the right video is (E). In figure 4, the user can find that the timeline (E) took longer time than (D) and the work efficiency of the user is not good. On the timeline, a colored rectangle shows an object that the user used at the timing. If the mouse pointer is over the colored rectangle, the system shows the picture of the corresponding object in (F). Since the same object has the same color, the user can easily recognize when the object was used in the two videos.



Figure 2. Video replay interface.



Figure 3. Video comparison interface

User can compare two different videos in the window as shown in figure 1. For example, the left is a video of an expert, and the right is a video of the user after the user watched the expert's video. The timeline of the left video is shown in the upper line, and that of the right video is the down. In figure 1, the user can find that the user took longer time than the expert and the work efficiency of the user is not good. On the timeline, a colored rectangle shows an object that the user used at the timing. If the mouse pointer is over the colored rectangle, the system shows the picture of the corresponding object. Since the same object has the same color, the user can easily recognize when the object was used in the two videos.

Figure 4 shows the video recommendation using LORAMS Gadget. The recommendation is based on the objects around the learner and his/her interests. If the learner clicks a video on the list, the video will be replayed in the web browser. We use TF*IDF method for the recommendation. The more the same object included the video, the higher the score of the recommendation is.



Figure 4. Video recommendation user interface

III. EXPERIMENT

This section describes the experiment on toy-making handicraft, which lasted for nine days. In this experiment, Experiment (2) functions plus the visual recommendation function under TF*IDF method and LORAMS Gadget (hereafter we call it Gadget) are implemented. We mainly examined these newly implemented functions.

The subjects are 15 students (3 seniors, 4 master course 1st years, 8 master course 2nd years). They were assigned to make two moving or flying toys out of daily materials such as disposable chopsticks, milk packages, cardboards (Figure 3). They competed the distance, how far they could make their toys run or fly. They learned the procedures through this system and Gadget. Fourteen kinds of tools and 17 kinds of materials were used for making toys.



Figure 5. Environment for the subjects

A. Methods and Purposes

We followed the steps as shown below:

(i) Pre-meeting of the participants

They received the briefing about the competition rules, the whole schedule, and guidance to the system.

(ii) Toy-Making (First Try) (cf. Figure 4)

Each subject made a toy only with the help from the written manual and let it run. They were supposed to make it within 10 minutes. All the procedures were video-recorded and shared by the participants. Tag was read by the examiner for the purpose of convenience.

(iii) Learning through the system and making improvements
After (ii) was done, each subject made use of the system and Gadget and learned through watching other participants' procedures. While watching, they were asked to write down the video files they thought were helpful. Meanwhile they were free to make an improvement on their own toys, video-record their improved ones and share the videos.

(iv) Toy-Making (Second Try)

After learning through watching videos, they gave it the second try to make toys. Every procedure was video-recorded and shared by the participants.

(v) Post-Questionnaires

Each subject was asked to pick out helpful video files and evaluate the systems including interface design.

In Step (iii), each subject's number of times of access to the video files was counted and the usage rate was calculated. In Step (iv), it was examined whether or not they made any improvement on their moving/flying performance compared with their first toys. In Step (v) they picked out three helpful videos and it was examined whether helpful videos would be recommended by the recommendation system.



Figure 6. Figure 4: Toys made by the subjects.

B. Results and Discussions

Handicraft videos accumulated up to 37 including the ones made by the examiners. Totally 89 videos were uploaded and shared. During the experiment, the users visited and watch them 204 times in all.

Table 1 shows some of the handicraft toys made by the participants. The best record, 6.7m was made by the car powered by air-balloon. Table 1 shows the trial records and the results of the post-questionnaires are shown in Table 4.6.

TABLE I. RECORDS

Trial	Average Record	Best Record	Worst Record
1 st trial	0.67m	4.80m	0.00m
2 nd trial	2.59m	6.70m	0.05m
2 nd trial - 1 st trial	1.92m	1.90m	0.05m

TABLE II. POST-QUESTIONNAIRE RESULTS

	Questions	Avg	SD
Q1	Was the system supportive in making toys?	4.57	0.65
Q2	Did you get new knowledge through the system?	4.43	0.51
Q3	Did the system let you find your mistakes thus help improve your second trial?	4.07	1.00
Q4	Was the search result interface user-friendly?	4.12	1.19
Q5	Was the video-browsing and annotation input interfaces user-friendly?	3.15	1.34

As Table 1 shows, the net increase of the average record was 1.92m and that of the best record was 1.90m. Judging from these results and their replies to Q1, Q2, Q3 shown in Table 4.6, we can safely say that the participants made use of our system and it contributed to the progress of their record through watching and learning shared videos.

As for interface evaluation, Table 2 Q4 shows the search result interface obtained comparatively high score, while Q5 shows the video-browsing and annotation input interfaces were not user-friendly. Its inconvenience was pointed out by some who say it was hard to know how to input annotations. But since another said that annotation was convenient because the users were able to add some comments or hints. Therefore it seems to be worth keeping it as a function. Still it is necessary to reconsider and improve annotation interface.

TABLE III. RESULTS OF GADGET QUESTIONNAIRES.

	Questions	Avg	SD
Q1	Was Gadget user-friendly?	3.93	1.27
Q2	Did Gadget help you notice newly uploaded videos?	3.86	1.17
Q3	Did Gadget disturb you?	3.14	1.03
Q4	Did you find Gadget necessary?	4.14	1.03
Q5	Did the recommendation function work well?	3.54	1.27

Their reply to Q 2 (Table 3) shows that we could provide the circumstance where the users could easily notice the newly uploaded video files. The users' comments included that Gadget pushed them to watch videos, that it was convenient to log in directly from Gadget, and that it was troublesome to make access to the web system. Its automatic log-in system, log-in by clicking the thumbnail picture received the most favorable comments from the users.

Among other comments, some say that the blinking light on the task bar drew their attention to notice new videos, while others say that it was annoying. So the same function works well to some, while not to others. It means that it might be necessary to make the system more adaptive to each user's needs.

Taking these things into account, with some problems to be solved, Gadget worked well enough as a tool to support LORAMS.

IV. CONCLUSION

Ubiquitous computing will be integrated into everyday objects and activities and support not only to provide the right information at the right time at the right place but also to capture, share and reuse human's experiences.

This paper proposes a ubiquitous learning environment called LORAMS (Link of RFID and Movies System), which supports the learners with a system to share and reuse learning experience by linking videos and environmental objects. The system has the following features:

- (1) Without any text annotation, the learner can find the suitable scenes that include the objects around the learner.
- (2) The system recommends the learners the suitable videos for watching and comparing according to the numerical ranking methods that are proposed in this paper.
- (3) The system allows the learners to share knowledge through making annotations into videos.

In future work, we will improve the user interface and ranking methods based on the students' comments. Also we believe LORAMS can be applied to many domains in which a person needs several kinds of objects and skills to do a task, and the result varies depending on the objects and the skills used in the task; for example, checking upon cars such as oils, battery, and tires, second language learning for the people who are living in a foreign country, or surgery operations and chemical bioreactor experimentations.

ACKNOWLEDGMENT

This research work was partly supported by JST PRESTO (Sakigake), and the Grant-in-Aid for Scientific Research No. 18700651 and 21650225 from the Ministry of Education, Science, Sports, and Culture in Japan.

REFERENCES

- [1] Abowd, G.D., & Mynatt, E.D. (2000). Charting Past, Present, and Future Research in Ubiquitous Computing. *ACM Transaction on Computer-Human Interaction*, 7(1), 29-58.
- [2] Borriello, G. (2005). RFID: Tagging the World, *Communications of the ACM*, 48(9), 34-37.
- [3] Lyytinen, K., & Yoo, Y. (2002). Issues and Challenges in Ubiquitous Computing, *Communications of ACM*, 45(12), 63-65.
- [4] Ogata, H., & Yano, Y. (2004). Context-Aware Support for Computer-Supported Ubiquitous Learning, *Proc. IEEE International Conference on Wireless and Mobile Technologies in Education (WMTE2004)*, 27-34.
- [5] Ogata, H., Matsuka, Y., El-Bishouty, M.M. & Yano, Y. (2007). LORAMS: Linking Physical Objects and Videos for Ubiquitous Learning, *Proc. International Conference on Computers in Education (ICCE 2007)*, 297-304.
- [6] Sakamura, K. & Koshizuka, N. (2005). Ubiquitous Computing Technologies for Ubiquitous Learning. *Proc. IEEE International Workshop on Wireless and Mobile Technologies in Education (WMTE2005)*, 11-18.